



Note vulnerable properties : Refers to the degree of wear and tear in the day-to-day operation of the correct use of this part which according to guide customers reasonable reserves.A for wear and tear easily, B for wear and tear is not easy while C for wear and tear on behalf of the non-basic.The part of A proposal by the highest parts inventory reserves; B for stocking pieces according to the minimum reserves and C try not to make reserves for.

Model:LC2P80F		Description	Code Number : T390002635-1909034	LC/LT-2024-A	
No.	Part No.			Reqd. QTY	CONSUMABLE GRADE
1	195360010-0003	Starter outer cover	T390;	1	B
2	160210044-0001	Fan cover comp.	T390;	1	B
3	380020086-0001	Hexagon shaft shoulder bolt	T390_M6×16.8(Φ8×5.8);Q16	3	C
4	380020087-0001	Hexagon shaft shoulder bolt	T390_M6×21.8(Φ8×10.8);Q16	1	C
5	380140451-0001	Hexagon bolt with flange	GB/T 5789_M8_L=20_S=12;Q16	6	C
6	160180020-0001	Impeller	T390;	1	B
7	380140457-0001	Hexagon bolt with flange	T390_M12×1.25_L=35_Q16	1	C
8	380450702-0001	Flat washer	T390_13_38_3.5;Q07	1	C
9	270020290-0001	FLYWHEEL COMP	T400_;	1	B
10	380190039-0005	Socket head screw	GB/T 70.1_M6_L=25;Q16	4	C
11	270190054-0001	Components of charging current armature	T400_B	1	B
12	380140013-0005	Hexagon bolt with flange	GB/T 5789_M6_L=16;Q16	24	C
13	160200061-0001	Side plate	T400;	1	C
14	110840013-0001	CAP,BREATHER CHAMBER	T390;	1	C
15	110850012-0001	PACKING, BREATHER CHAMBER	T390;	1	A
16	171610038-0001	throttle return spring	T400_B	1	A
17	380140453-0001	Hexagon bolt with flange	GB/T 5789_M8_L=80_S=12;Q16	2	C
18	120550002-0001	Lifting eye	T390_A;	1	C
19	270360170-0001	Components of starting motor	T400_1/4-20 UNC-2A;	1	B
20	380140077-0005	Hexagon bolt with flange	GB/T 5789_M6_L=20;Q16	4	C
21	270920354-0002	COIL ASSY.,IGNNTION	T400_ .B	2	B
22	380140067-0003	Hexagon bolt with flange	GB/T 5789_M6_L=12;Q16	4	C
23	140250008-0001	Leaf valve	T390;	1	B
24	380650337-0001	Oil seal	T110_d=35_D=52_b=7;Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	1	B
25	160190037-0001	air deflector	T390_	1	C
26	110690043-0001	Oil rule combination	T390-24QJ6	1	B
27	271930021-0001	Rectifier	T390_	1	B
28	380900061-0002	Strap	T560_L=195_	3	A
29	160190036-0001	air deflector	T390_	1	C
30	150840002-0002	Oil filter Mounting bolts	T381;	1	C
31	150350046-0002	Oil filter	T400;ROHS	1	B
32	110810095-0001	Crankcase body	T390_	1	B
33	140690017-0001	Lifter, Valve	T390;	4	B
34	140670037-0001	Push rod	T09J_156_	4	B
35	120150288-0001	Gasket for cylinder head	T390_	2	A
36	380600129-0001	ocation pin	T130_d=12_L=15;	4	C
37	500550037-0001	Valve Kit	T390;	2	B
38	120080742-0001	Cylinder head	T390_	1	B
39	170430106-0001	Carburetor gasket	T390_	2	A
40	270960046-0001	Spark plug	RN9YC;	2	A
41	380140455-0001	Hexagon bolt with flange	T390_M10×1.25_L=70_Q16	6	C
42	380140456-0001	Hexagon bolt with flange	T390_M10×1.25_L=50_Q16	4	C
43	140360010-0001	Seat, valve spring	T110;Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	4	B
44	140400012-0001	Valve oil seal	T110;Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	4	B
45	140340025-0001	Inner spring of valve	T11D_Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	4	A
46	140380021-0001	Retainer, valve spring	T11D_Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	4	B
47	140390015-0001	Valve locker	T11D;Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	8	B
48	140710014-0001	Plate, push rod guide	T390_EPA3;	2	B
49	140450035-0002	Valve rocker combination	T390;	4	B
50	120250061-0001	Gasket for cylinder head cover	T400_9016;	2	A
51	120220025-0001	Cylinder head cover assy	T390;	2	C
52	380140103-0004	Hexagon bolt with flange	GB/T 5789_M6_L=25;Q16	8	C
53	120550003-0001	Lifting eye	T390_B;	1	C
54	380740633-0002	Breather tube	T390 ROHS	1	A
55	170460026-0001	Gasoline pump	T381_B	1	B
56	170470006-0001	Gasoline pump bracket	T390;	1	C
57	380960287-0001	Clip combination	T400_Φ11.5;Q19	4	B
58	171600111-0001	Governing spring	T400_B;	1	A
59	170010045-0001	Fuel filter	T400_;	1	A
60	171630013-0001	Speed regulating arm	T390;	1	B
61	380450559-0001	Flat washer	T370_8_16_0.5;Q16	2	C
62	380650339-0001	Oil seal	T110_d=8_D=14_b=4;Hg/Cr6/Pb/PBB/PBDE≤1000ppm,Cd≤100ppm	1	B
63	381350004-0001	Pin clip	T040_	1	B
64	171620068-0001	Speed regulating bracket	T400_DQ16	1	C
65	173090003-0001	Locker of choke valve pull rob	T400;	2	A
66	171610028-0001	throttle return spring	T400_140.8,42;	1	A
67	171680144-0001	Throttle handle combination	T400_	1	B
68	380140100-0003	Hexagon bolt with flange	GB/T 5789_M6_L=35;Q16	4	C
69	180420647-0001	Intake pipe	T400_	1	C
70	380180116-0001	Stud	T52K_M6_L=106;Q16	4	C
71	170430107-0001	Carburetor gasket	T390_	2	A
72	170440073-0001	Heat insulating pad for carburetor	T390_	1	B
73	171590040-0001	Throttle rod	T390_72.5,φ2.5;	1	B
74	170022432-0001	Carburetor	T390_EPA3.;G2	1	B
75	380751120-0002	Oil tube	T390_6.35_12.7_200_REACH	1	A
76	380841074-0001	Seal ring	T390_	1	A

77	180010123-0002	Air filter	T390_B(180100109)/REACH	1	B
78	380370066-0001	Hexagon nut with flange	GB/T 6177.1_M6;Q16	4	C
79	380740632-0002	Breather tube	T390_ROHS	1	A
80	380460001-0006	Elastic washer	GB/T 93_d=8;Q16	4	C
81	380340005-0005	Hexagon nut	GB/T 6170_M8;Q16	4	C
82	380750596-0001	Oil tube	T381_内径6.35 12.7 130_CARB;EPA	1	A
83	180650074-0001	Outlet gasket	T370_	2	B
84	180990115-0001	Muffler bracket	T400;	1	C
85	180571314-0001	Muffler	T390;	1	B
86	120080741-0001	Cylinder head	T390_	1	B
87	130290226-0001	crankshaft	T390_A	1	B
88	130150073-0001	Connecting rod	T390;	2	B
89	130060054-0001	Piston pin	T390_φ17×54.6;	2	B
90	380560078-0001	Steel cable baffle ring	T390_	4	B
91	130030226-0001	Piston	T390_EPA3;	2	A
92	130070157-0001	Piston ring combination	T09J_-1.2;	2	A
93	150340012-0001	Cover,Oil Strainer	T390;	1	C
94	150290019-0001	Engine oil Strainer	T390;	1	B
95	120530005-0001	Pressing plate for oil groove	T390_	1	A
96	380600123-0001	ocation pin	T370_d=10_L=12;	2	C
97	120530006-0001	Pressing plate for oil groove	T390_	1	A
98	381150437-0001	Compression spring	T390_	1	A
99	380640016-0001	Steel ball	GB/T 308_Φ9.5;	1	C
100	380840443-0001	Seal ring	T370_D=11.7_d=2.5_;	2	A
101	110830034-0001	Crankcase cover gasket	T390;	1	A
102	110260088-0002	Sealing plug screw	T381_3/8-18NPTF_Q16	2	C
103	171750053-0001	Components of governor gear	T390_PA66-30GF_9.5g_B;	1	B
104	140020130-0001	Camshaft assy	T400_	1	B
105	110820172-0001	Crankcase cover	T390_	1	C
106	150570003-0001	Engine oil return block	T370_	1	A
107	380650436-0001	Oil seal	T390_d=35_D=62_b=8_VITON;	1	B
108	150010084-0001	Components of oil pump	T400;	1	B
109	380841159-0002	Seal ring	T390_D=47_d=3.5_REACH	1	A
110	150040025-0001	Oil pump cover	T390;	1	C
111	380140338-0001	Hexagon bolt with flange	T030_M8_L=55;Q16	10	C
112	283690002-0001	Oil level alarm	T390_(0.02~0.06)MPa;	1	B
113	380900062-0001	Strap	T561_L=100_;	1	A
114	380940461-0001	Cable cleat	T390_	1	B
115	380840943-0001	Seal ring	T390_D=17.3_d=3	1	A
116	380840944-0001	Seal ring	T390_D=18_d=2.65_	1	A
117	180100109-0001	Air filter element combination	T390_B	1	A
118	381000305-0001	Caulking	T400_	1	A
119	170420003-0001	Solenoid valve	T390	1	A
120	380180109-0001	Stud	T240_M8_L=39;Q16	4	C
121	171650036-0001	Choke valve pull rod	T400;	1	B
122	271280133-0001	Connecting wire	T390	1	A
123	110950004-0001	Joint of extension bar for bleeding	T400_B	1	C
124	292980115-0001	tube comp.	T390_	1	A
125	174560002-0001	Filter block	T390;	1	A
126	380770343-0001	Protective sleeve	T390_14_0.5_150_REACH	1	A
127	380960120-0004	Clip combination	T040_Φ12_Q19_REAC	1	A